

SPM-160/210/260 HORIZONTAL PREMADE POUCH PACKING MACHINE



Speed up to 50 bags per minute!



FEATURES

- Automatic Pick & Place bag infeed system
- Siemens PLC control with touch screen operation
- Multi-Language HMI
- Date Coding
- 304 stainless steel frame
- Product detection – no filling, no sealing
- Two-step sealing process guarantees clean sealing

OPTIONS

- Various filling systems for powder, granule, liquid, snacks, herbal or other customized products
- Zipper opening & Sealing device
- Metal detectors
- Checkweigher
- Bag deflators
- Dust suction nozzles and dust collector
- Material infeed conveyor
- Collating discharge conveyor
- Ethernet connectivity
- Automatic deoxidizer & spoon feeding station



SPECIFICATIONS

Model	SPM-160	SPM-210	SPM-260
Air Consumption	0.7 m³/min		
Dimensions	2135 x 1330 x 1460 mm (84 x 52 x 54")		2750 x 1450 x 1460 mm (108 x 57 x 57")
Packing Speed	30-50 bags/min	20-50 bags/min	10-40 bags/min
Machine's Material	304 Stainless Steel		
Voltage	380V 50/60Hz		
Machine Weight	600KG (1322lbs)	800KG (1764lbs)	900KG (1984lbs)
Packaging Size	Length: 110-230 mm (4.3-9.0") Width: 90-160 mm (3.5-6.3")	Length: 110-320 mm (4.3-12.6") Width: 85-210 mm (3.3-8.3")	Length: 110-360 mm (4.3-14.2") Width: 120-260 mm (4.7-10.2")
Bag Film Material	Laminated film, laminated paper film, aluminum foil film		
Bag Optional Features	Hanging hole, euro slot, carry handle, degassing valve, tear notch, zipper, spout		

